

AP-IPC-DM50L2-E

ACTIVE pixelTM
safety made easier



Key Features

- **IP 5.0 MP DOME CAMERA**
- 1/3" Progressive scan CMOS sensor
- Max. 2944 × 1656@20fps
- Video System NTSC/PAL
- FULL HD Fixed 3.6mm, 6mm Optional Lens
- 20 to 30 meter illumination
- Support Tri-stream
- Auto IR cut filter with auto switch
- ONVIF / PoE optional / IP66

AP-IPC-DM50L2-E

ACTIVE pixelTM
safety made easier

S P E C I F I C A T I O N

Model	AP-IPC-DM50L2-E
Image Sensor	1/2.9" Progressive Scan CMOS
Minimum Illumination	Color: 0.01 lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON), 0 lux with IR
Shutter Speed	1/3 s to 1/100,000 s
White Balance	Auto/Manual
Lens	3.6mm (2.8mm, 6mm optional)
S/N Ratio	More than 50dB
Video Streaming	50Hz: 20 fps (2944 × 1656), 25 fps (2560 × 1440, 1920 × 1080, 1280 × 720) 60Hz: 20 fps (2944 × 1656), 30fps (2560 × 1440, 1920 × 1080, 1280 × 720)
Resolution	2944 × 1656
Privacy Mask	Up to 4 areas
ICR	Auto(ICR)/Color/B/W
Audio Input	1 Ch
Audio Compression	G.711a
Protocol	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6
Ethernet	RJ-45 (10/100Base-T)
User Account	20 Users
Smart Phone	iPhone, iPad, Android
IR	IR Range of 30 Mtr.
Operating Temperature	-40°C~+60°C, Less than 95% RH
Power Source	DC12V, PoE optional
Power Consumption	Max 5W
Weatherproof Standard	IP66