

AP-3200-N-H.265

ACTIVE pixelTM
safety made easier

32CH



H.265
NVR
NETWORK VIDEO RECORDER



Key Features

- 16/24/32CH IP camera inputs, Compatible with 5/4/2/1.3/1MP.
- 1CH VGA, 1CH HDMI.
- Audio In / Out Supported.
- Alarm: 6CH In, 1CH Out, Sync Play back: 4CH 1080P/960P/720P
- 4 SATA, (6TB), USB 2.0+USB 3.0, 1 RJ45 (10/100/1000M), RS-485.

AP-3200-N-H.265



Feature	Specification
Processor	Dual-core embedded processor
Operating System	Embedded LINUX
IP Camera Input	32 channel
Two-way Talk	1 channel Input, 1 channel Output, RCA
User Interface	GUI
Video Output	1 HDMI, 1 VGA
Compression	H.265
Video Resolution	2560 × 1920, 2048 × 1536, 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
Video Recording	Max 128 Mbps
Motion Detection	MD Zones: 396(22×18)
Video Loss	Supports
Camera Blank	Supports
Alarm Input	16 channel
Alarm Output	4 channel
Hard Disk	4 SATA ports, up to 16TB, Raid (Redundancy), 1 eSATA port
Smart Phone	iPhone, iPad, Android, Windows Phone
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Recording Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Internal SATA burner/ Network
Interface Ports	1 HDMI, 1 VGA, 2 USB2.0, 1 RS485, 1 RS232, 1 RJ45
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Max User Account	128 users
Ethernet	1 RJ-45 port (10/100M/1000M)
Protocols	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter,PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3
Power Supply	AC 100V~240V,50/60HZ
Power Consumption	40W(without HDD)
Working Temp	-10 ~+55°C / 10~90%RH / 86~106kpa