

AP-6400-N-H.265+

ACTIVE pixelTM
safety made easier

64CH



H.265+
NVR
NETWORK VIDEO RECORDER



Key Features

- Input-24*5MP/36*4MP/64*2MP
- Output : VGA, HDMI up to 3840*2160 Resolution
- Audio In/Out Supported
- Alarm:16CH In, 4CH Out, Sync Play back: 4CH 5MP/9CH 4MP/8CH 1080P
- 8 SATA(8TB), USB2.0+USB 3.0
- 1RJ45(10/100/1000M),RS-485.
- ONVIF Support

AP-6400-N-H.265+



Feature	Specification
Processor	Dual-core embedded processor
Operating System	Embedded LINUX
IP Camera Input	64 channel
Two-way Talk	1 channel Input, 1 channel Output, RCA
User Interface	GUI
Video Output	1 HDMI, 1 VGA, 1TV
Compression	H.264 / MJPEG
Video Resolution	1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
Motion Detection	MD Zones: 396(22x18)
Video Loss	Supports
Camera Blank	Supports
Alarm Input	16 channel
Alarm Output	6 channel
Hard Disk	8 SATA ports (8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB, Raid (redundancy), 1 eSATA port (Max 4 SATA HDDs), up to 16TB
Smart Phone	iPhone, iPad, Android, Windows Phone
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Recording Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / eSATA Device / Internal SATA burner/ Network
Interface Ports	1 HDMI, 1 VGA, 1TV, 4 USB2.0, 1 RS485, 1 RS232, 2 RJ45
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Max User Account	128 users
Ethernet	2 RJ-45 port (10/100M/1000M)
Protocols	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.2
Power Supply	AC 100~240V, 50/60 Hz
Power Consumption	75W(without HDD)
Working Temp	-10 ~+55°C / 10~90%RH / 86~106kpa