

AP-BL1080P-L2-PIR

ACTIVE pixelTM
safety made easier



ACTIVE PIXEL
ANALOG HIGH DEFINITION
AP-AHD

HD 2MP PIR
C A M E R A

FEATURES

- Using the high performance sensor, image is clear and delicate
- High Definition HD 2.0MP real-time video optional
- Support AHD/CVI/TVI output optional
- HD video output, no delay, lossless, long distance transmission
- Reach 500 meters coaxial cable real-time transmission
- Support 3D noise reduction
- Built in 3-Axis Bracket, 4mm fixed megapixel lens

SPECIAL FEATURES

- Motion detect, frighten intruder
- Upgraded Dual light HD PIR Camera, added Light Flash, Buzzer Alarm
- PIR Motion Sensor, Intrusion detection
- Upgraded PIR detection, human, animal, vehicle, reduce false alarm
- Improved the alarm sensitivity, light on simultaneously when received PIR induction
- Support Light Flash, Buzzer Alarm two mode alarm optional.
- High performance color re-production
- Special 4-Port PIR video cable, Remote Controller
- PIR Sensitivity Distance: 6~8Meter

www.activepixel.in

AP-BL1080P-L2-PIR



S P E C I F I C A T I O N

Model	AP-BL1080P-L2-PIR
Resolution	1920*1080P Resolution
Image Sensor	2.0 Megapixel Sensor
Effective Pixels	2.0MP, 1920x1080P
TV System	PAL/NTSC
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s
Sync System	Internal
Usable Illumination	0.01Lux
Scanning System	Progressive Scan
S/N Ratio	≥50Db
Gamma Ratio	>=0.45
Video Output Mode	AHD/CVI/TVI(BNC)
Focus Length	4mm Fixed lens
Pixels	3M Pixels
LED board	2PCS White Light+2PCS ARRAY IR LED
IR Distance	20-25 meter
PIR Distance	6-8 meter
PIR induction angle	160°
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control
White Led Power On	Motion detected
White Light mode	Keep on(default), Flash
Buzzer	On, Off (default)
Buzzer power on	Motion detected
Day/Night	Auto (ICR) / Color / B&W
White Balance	Auto/Manual
Gain Control	Auto
Noise Reduction	3D NR
PClient	CMS
Cloud App	SKY AP
Weatherproof Housing	IP66 waterproof
Operation Temperature	-10°C~ +50°C RH95% Max
Power Source	DC12V±10%