

AP-IPC-BL20-10X (2MP)

**ACTIVE pixel**<sup>TM</sup>  
safety made easier



## Key Features

- **IP 2.0 MP-10X/BULLET CAMERA**
- 1/2.8" Progressive scan CMOS sensor
- 1920\*1080 Resolution, 2.0 MP
- Video System NTSC/PAL, Optical Focus 10X
- Focus Length 5-50mm, IR Distance 60m
- 255 Presets
- 0.01 Lux @ F1.6, AGC ON, 0 Lux with IR
- Auto IR cut with Auto Switch
- ONVIF support, IP66

**AP-IPC-BL20-10X/(2MP)**

**ACTIVE pixel**<sup>TM</sup>  
safety made easier

**S P E C I F I C A T I O N**

<b>Model</b>	<b>AP-IPC-BL20-10X(2MP)</b>
<b>Product Name</b>	1/2.8" 2MP CMOS ICR Day and Night PTZ Zoom IP Camera
<b>Image Sensor</b>	1/2.8" Progressive Scan CMOS
<b>Mini Illumination</b>	0.00 Lux @(F16.AGC ON), 0Lux with IR
<b>Electronic Shutter Speed</b>	1/25-1/100,000S
<b>Lens</b>	1/2.8 10X Zoom, auto focus, 5 to 50mm
<b>Focus</b>	1-10x real time continuously
<b>Lens Mount</b>	M12
<b>Day/Night</b>	IR-CUT
<b>Compression Standard</b>	H.264
<b>H.264 Cord Type</b>	BaseLine Profile / Main Profile
<b>Bit Rate</b>	1000Kbps~6000Kbps
<b>Max Photo</b>	1920 x 1080
<b>Resolution</b>	25fps (1920 x 1080), 30fps (1920 x 1080)
<b>Picture Set</b>	Saturation, Brightness, Contrast Adjustable through client software or IE browser
<b>Horizontal rotation angle</b>	0°~300°
<b>Vertical rotation angle</b>	-5°~60°
<b>Horizontal rotation Speed</b>	0.5°~24°/s
<b>Vertical rotation Speed</b>	0.5°~24°/s
<b>Presets</b>	255
<b>Port Protocol</b>	ONVIF
<b>Alarm</b>	Motion detection, Dynamic analysis, Occlusion alarm
<b>Protocol</b>	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6
<b>Communication Inter face</b>	1pc RJ45 10M / 100M Ethernet
<b>Power Supply</b>	DC12V±10%
<b>Power Consumption</b>	6.5W MAX(ICR switch moment 8.5W)
<b>Waterproof</b>	IP66
<b>Bracket</b>	Wall install bracket
<b>IR Distance</b>	60 meters