

AP-IPC-BLVF40L4

**ACTIVE pixel**<sup>TM</sup>  
safety made easier

**MOTORIZED**  
**ZOOM**



## Key Features

- **IP 4.0 MP BULLET CAMERA**
- 1/3" Progressive scan CMOS
- Support H.264 & H.265 MJPEG dual codec
- Max 20fps@4MP (2688x1520), 25/30fps@3M (2304x1296)
- Smart Detection Supported
- WDR (120dB), Day/Night (ICR), 3DNR, AWB, AGC, BLC
- 2.7mm – 12mm Motorized Lens
- Max. IR LEDs Length 50m
- IP67, PoE optional

# AP-IPC-BLVF40L4

**ACTIVE pixel**<sup>TM</sup>  
safety made easier

## S P E C I F I C A T I O N

<b>Model</b>	AP-IPC-BLVF40L4
<b>Image Sensor</b>	1/3" 4 MP CMOS Image Sensor
<b>Minimum Illumination</b>	0.01Lux@F1.2(Color)/0.001Lux@F1.2(B/W)
<b>White Balance</b>	Auto/Manual
<b>Lens</b>	2.8-12mm Motorized Lens
<b>AGC Control</b>	Auto/Manual
<b>Video Compression</b>	H.265/ H.264
<b>Back Light Comp.</b>	Auto/Manual / WDR(100dB)
<b>Video Streaming</b>	Dual-stream
<b>Resolution</b>	4M(2560x1440) / 3M(2048x 1536)/1080P(1920x 1080) / 720P(1280x 720) /D1(704x 576) /CIF(352x 288)
<b>Frame Rate</b>	Main Stream: 4MP@25fps, Sub-Stream: D1
<b>ICR</b>	supports
<b>Audio Input</b>	1 Channel
<b>Audio Output</b>	1 Channel
<b>Alarm IN</b>	1 Channel
<b>Alarm Out</b>	1 Channel
<b>Protocol</b>	ONVIF Support (profile S)
<b>IR</b>	IR Range of 50 Mtr.
<b>Operating Temperature</b>	- 20°C~ 65°C
<b>Power Source</b>	DC12V±10%,PoE
<b>Weatherproof Standard</b>	IP67