

AP-IPSY30X-2.0MP

ACTIVE pixelTM
safety made easier

2MP



Key Features

- **IP 2.0 MP-PTZ SPEED DOME**
- 1/3" CMOS Sony323
- 1920*1080 Resolution 2MP
- Color:0.5Lux, B/W:0.05Lux, IR ON:0Lux
- 30X Optical Zoom, 4.7mm~94mm
- IR Distance up to 200 meter (18pcs LED)
- Focus Length 4.5 to 162mm
- Indoor: 0°~ +40°, Outdoor: -40°~ +60°
- Max 180/s pan speed, DC12V(3A), 35W, IP66

AP-IPSY30X-2.0MP



SPECIFICATION

Model	AP-IPSY30X-2.0MP
Image Sensor	1/3" CMOS Sony323
Effective Pixels	1944(H) x 1092(V), 2 Megapixels
Video Output	BNC(1.0Vp-p/75Ω), PAL / NTSC
S/N Ratio	More than 50dB
Minimum Illumination	Color: 0.05Lux@F1.6, B/W: 0.005Lux@F1.6
Focal Length	4.3mm~129mm
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Focus Control	Auto / Manual
Angle of View	H: 65.1° ~ 2.34°
Electronic Shutter	1/1 ~ 1/30,000s
AGC Control	Auto / Manual
Back Light Compensation	BLC / HLC / DWDR
Optical Zoom	30x
Digital Zoom	16x
Pan Travel	360° endless, Pan Speed: 0.1° ~ 160°/sec
Tilt Travel	-15° ~ 90°, Tilt Speed: 0.1° ~ 120°/sec
Presets	255
Preset Speed	Pan: 240° /s; Tilt: 200° /s
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/ Pan/ Scan/ Tour/ Pattern if there is no command in the specified period
Time Task	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time
Day/Night: IR Cut Filter	Auto(ICR) / Color / B/W
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream: 25/30fps@1080P/720P, Sub Stream: 25/30fps@D1/CIF
Audio Compression	G.711a / G.711u(32kbps)/ PCM(128kbps)
Audio Streaming	1/1 channel In/Out
Protocols	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
Alarm	2/1 channel In/Out
Smart Phone	iPhone, iPad, Android, Windows Phone
Operating Temperature	-40°C ~ 60°C / Less than 90% RH
Weatherproof Standard	AC 24V/2.2A(±10%)
Power Source	IP66
Power Consumption	10.5W, 26W (IR on, Heater on)
Memory	Micro SD, Max 64GB
Optical Zoom	30x