

AP-IPSY36X-2.0MP(mini)

**ACTIVE pixel**<sup>TM</sup>  
safety made easier

2MP



5 INCH



## Key Features

- **IP 2.0 MP-PTZ SPEED DOME**
- 1/2.8" Progressive scan CMOS sensor
- 1920\*1080 Resolution
- Color : 0.01 Lux @ F1.2
- 36X Optical Zoom
- IR Distance up to 150 meter
- Focus Length 4.5 to 162mm
- IP66, -40°~60°C
- Max 180/s pan speed
- DC12V(3A), 35W, IP66

# AP-IPSY36X-2.0MP(mini)



## SPECIFICATION

Model	AP-IPSY36X-2.0MP(mini)
Image Sensor	1/2.8" Progressive scan CMOS sensor
Effective Pixels	1920*1080
Lens	3.25-88.5mm
Iris	F1.6~F4.5
Optical zoom	36X Optical zoom
IR-CUT	YES
IR Distance	100-150m
IR LED	8pcs LED
Min illumination	color: 0.05Lux/F1.6, B/W: 0.005 Lux/F1.6, 0Lux(IR)
Image Compression	H.264
Image frame rate	1920*1080
BLC	ON/OFF
WB	Auto / Manual / One Touch WB / ATW
SN	50dB (AGC OFF)
Proportional Zoom	Rotation speed can be adjusted automatically according to zoom multiples
Pan Range	360° endless
Pan Speed	0.6°~200°/s
Tilt Range	0°~90°, auto flip 180°
Tilt Speed	3.5°~35°/s
Number of Preset	220
Patterb	4 patterns, with the recording time not less than 10 min per pattern
3D Position	Yes
Alarm	4CH alarm input and 2CH relay output
Supported Protocol	TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, RTSP, PPPoE, SMTP, NTP (FTP, SNMP optional)
Ethernet	Rj45 10Base-T, / 100Base-TX
Operate Temp	-30°C ~ 65°C (-22° F ~ 149° F)
Operate Humidity	10% ~ 80% non-condensing
Power Supply	DC12V±10% (AC24V±10% optional)
Power Consumption	45W MAX
Protection	IP66 with TVS 4000V lightning protection, surge protection and voltage transient protection
Storage Humidity	0% ~ 90% non-condensing
Certification	CE RoHS FCC
Warranty	2 year warranty