

AP-IPSY36X-5.0MP

ACTIVE pixelTM
safety made easier

5MP



Key Features

- **IP 5.0 MP-PTZ SPEED DOME**
- 1/2.7" Progressive scan CMOS sensor
- 2560*1960 Resolution
- Color: 0.01 Lux B/W: 0.001 Lux
- 36X Optical Zoom
- IR Distance up to 150 meter
- Focus Length 4.5 to 162mm
- Max 180/s pan speed
- DC12V(3A), 35W, IP66-40°~60°C

AP-IPSY36X-5.0MP



SPECIFICATION

Model	AP-IPSY36X-5MP
Image Sensor	1/2.7" Progressive scan CMOS sensor
Effective Pixels	2560(H) x 1920(V), 5 Megapixels
Video Output	BNC(1.0Vp-p/75Ω), PAL / NTSC
S/N Ratio	More than 55dB
Minimum Illumination	Color: 0.01Lux@F1.5; 0Lux@F1.5(IR on)
Focal Length	6mm ~ 180mm
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Focus Control	Auto / Manual
Angle of View	H: 61.2° ~ 2.1°
AGC Control	Auto / Manual
Back Light Compensation	BLC / HLC / DWDR
Optical Zoom	36x
Pan Travel	0° ~ 360° endless, Pan Speed: 0.1° ~ 200°/sec
Tilt Travel	-20° ~ 90°, auto flip 180°, Tilt Speed: 0.1° ~ 120°/sec
Manual Speed	Pan: 0.1° ~ 200° /s; Tilt: 0.1° ~ 120° /s
Presets	300
Preset Speed	Pan: 240° /s; Tilt: 200° /s
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/ Pan/ Scan/ Tour/ Pattern if there is no command in the specified period
Day/Night: IR Cut Filter	Auto(ICR) / Color / B/W
Video Compression	H.265/H.264 / MJPEG
Video Streaming	Main Stream: 5M/3M/1.3M/720P(1~25/30fps), 1080P(1~50/60fps), Sub Stream1: D1/CIF(1 ~ 25/30fps), Sub Stream 2: 5M(1~20fps), 1080P/1.3M/720P(1~25/30fps)
Audio Compression	G.711a/G.711Mu/AAC/G.722/ G.726/ MPEG2-L2
Auto Tracking	Support
Audio Streaming	1/1 channel In/Out
IVS	Tripwire, Intrusion, Abandoned/Missing, Face Detection
Networking	RJ-45 (10/100Base-T), 1RS485
Protocols	IPv4/IPv6,HTTP,HTTPS,SSL,TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x, ONVIF, PSIA, CGI
Alarm	7/2 channel In/Out
Smart Phone	iPhone, iPad, Android Phone
Operating Temperature	-40°C ~ 70°C / Less than 95% RH
Weatherproof Standard	IP67, IK10
Power Source	AC24V/3A(±25%), Hi-POE
Power Consumption	24W, 38W (IR on)
Memory	Micro SD Card 128GB
Optical Zoom	20x
Dimension - (WxLxH)	12"x9"x20"