

AP-IPVY30X-2.0MP

**ACTIVE pixel**<sup>TM</sup>  
safety made easier

2MP



## Key Features

- **IP 2.0 MP-WIPER PTZ SPEED DOME**
- 1/3" HI3516C+SONY323
- 1920\*1080 Resolution 2MP
- Color: 0.01 Lux B/W: 0.001 Lux
- 30X Optical Zoom, IR LED 14pcs
- IR Distance up to 140 meter
- Focus Length 5.35mm~96.3mm
- IP66, -40°- +60°, Max 180/s pan speed
- AC/DC15-28V ≤2A, 20W, **WIPER**

# AP-IPVY30X-2.0MP



## SPECIFICATION

<b>Model</b>	<b>AP-IPVY30X-2.0MP</b>
<b>Image Sensor</b>	1/3" HI3516C+SONY323
<b>Effective Pixel</b>	1920*1080
<b>Optical Zoom</b>	30X
<b>Focal Length</b>	f=4.3-129mm
<b>Aperture Range</b>	F1.6-F3.5
<b>Angle of View</b>	61.4°-2.9°(Wide-Tele)
<b>Day&amp; Night</b>	ICR
<b>Focus Mode</b>	Auto /Manual
<b>S/N Ratio</b>	>52dB
<b>BLC</b>	ON/OFF
<b>White Balance</b>	Auto / Manual
<b>Shutter Time</b>	1/1s-1/30,000s
<b>AGC</b>	Auto/Manual
<b>Min. illumination</b>	Color:0.05Lux@(F1.6,AGC ON), B/W: 0.01Lux@(F1.6, AGC on )
<b>Max. Image Resolution</b>	1920*1080
<b>Frame Rate</b>	50Hz: 25 fps (1920×1080), 25 fps (1280×720), 60Hz: 30 fps (1920×1080), 30 fps (1280×720)
<b>Dual Stream</b>	Support
<b>Security Measures</b>	Password protection, multiuser access control
<b>Protocols</b>	TCP/IP,HTTP,DHCP,DNS,DDNS,RTSP,PPPOE,NTP,UPNP,SNMP,FTP,802.1x,QOS,HTTPS,IPv6(SRTP)ONVIF
<b>Interface</b>	1 network interface,1 power input
<b>IR Leds</b>	8 high power array IR leds
<b>IR Range</b>	120m
<b>IR Action Mode</b>	Auto/Manual/Camera
<b>IR Led Power</b>	18W
<b>Pan Range</b>	360° endless
<b>Pan Speed</b>	Pan Manual Speed: 0.01°-120°/s, Pan Preset Speed: 220°/s
<b>Tilt Range</b>	-5°-90° (Auto Flip)
<b>Tilt Speed</b>	Tilt Manual Speed: 0.1°-120°/s, Tilt Preset Speed:120°/s
<b>Number of Preset</b>	256
<b>Patrol</b>	8 patrols, up to 32 presets per patrol
<b>Auto Scan</b>	8 scans with stable left and right boundaries
<b>Pattern</b>	4 patterns, up to 500 instructions per pattern
<b>OSD Menu</b>	English / Chinese
<b>VAL</b>	Support
<b>Wiper</b>	Standard Configuration
<b>Power Box</b>	Optional
<b>Power Supply</b>	DC12V±10%
<b>Power Consumption</b>	38W
<b>Working Temperature/Humidity</b>	-35°C~+55°C 90% or less(No Condensing)
<b>Protection Level</b>	IP66 standard, Level 2 lightning protection, 4000V surge protection
<b>Mounting</b>	Various mounting modes option:wall-mount,pendant-mount
<b>Accessories</b>	Wall-mount bracket, Power adapter(DC12v)