

AP-PT-WIFI-CAM-01



**720P PTZ PAN/TILT, WIFI IP CAMERA, P2P IR NIGHT VISION
MONITORING SECURITY CAMERA**

. AP-PT-WIFI-CAM-01

- Easy installation and use, plug and play.
- View the video anytime and anywhere, Support multiple platforms, terminals, networks.
- Clear and smooth video, intelligent transmission.
- Bank level security control and ensure privacy.
- Online firmware upgrade, update function and experience synchronously.
- H.264 video compression, transmit HD video in narrow bandwidth. High picture quality, low bit stream, local HD video recording. Watch more smoothly and no streaking.
- Support two-way audio, telecommunication level of signal processing, (echo cancellation, noise suppression, comfort noise, silence suppression).
- Support Android /iOS system mobile devices, remote real-time monitoring.
- Motion detection, linkage snapshot/video recording, real-time App push notifications.
- Infrared night vision lighting(IR distance: 8 meters),24 hours day and night monitoring, IR-CUT switch.
- Support micro SD card (max 128 GB) storage, cloud box and cloud storage.
- Support QR code login.
- Support digital zoom.
- Support 2.4G WI-FI (IEEE802.11b/g/n).
- Support P/T/Z remotely (Horizontal:350°& Vertical:100°)

Model	AP-PT-WIFI-CAM-01
Display Resolution	1280*720 (1MP)
Lens	f: 3.6mm, 1.3MP
Visual angle	H:60.5°; V:37°; D:72°
Minimum illumination	0.01Lux
Input/output	Built-in microphone and speaker
Audio compression	AAC
Video compression	H.264
Lighting frequency	50Hz, 60Hz
Image frame rate	Max 30fps
Image resolution	1MP
Image adjustment	Brightness, Contrast, Saturation, Sharpness
White balance, BLC	Automatically
Night vision	6 dot matrix infrared lights, IR distance: 8meters
Wireless networks	2.4G WIFI(IEEE802.11b/g/n),Built in PCB board 2DB antenna
Ethernet	10/100Mbps
Protocols	TCP/IP, UDP/IP, HTTP, DHCP, RTMP, MUTP
Support connecting RF devices	No
Face detection	No
POE	No
Pan&Tilt	Horizontal:350°& Vertical:100°
Alarm detection	Motion detection
Alarm linkage	Snapshot, audio/video record
Alarm notification	Real-time App push notifications
RF Peripheral	No
Power	DC 5V/2A (Europen, UK, USA type for option) power consumption 7W
Buttons	A reset hole, a FN button
Network interface	RJ45
Adjustable lens	No
LED instructions	Network signal/function indicator
Video storage	Micro SD (Max 128GB), cloud box, cloud storage
Work temperature	-10° ~ 55°C (14°F ~ 131°F)
Work humidity	10% ~ 80% (No condensation)
Storage temperature	-10°C ~ 60° (14°F ~ 140°F)
Storage humidity	0% ~ 90%(No condensation)
Color	White and black
Size(L*W*H)	85(L)X85(W)x120(H)mm
Weight	267g (not include rack)
Certificate	RoHS,CE,FCC,NCC



IR-CUT



Wi-Fi



HD LENS



Mobile View



Spy Motion Alarm



Looping record



Infrared night vision



Two way audio



Motion Detection



128GB SD Card



Plug and Play



Android



Apple